



The new Laird Technologies M8 vehicle mount for TETRA whip antennas reaffirms a commitment to the Public Safety and Land Mobile Radio market. The M8 vehicle mount base is an industry standard and whip antennas can be easily interchanged due to the modularity of the design.

The Laird Technologies M8 base and whips are molded with high impact, UV resistant polycarbonate material and use high-quality coaxial cables and connectors.

FEATURES

- Designed for rugged environments
- Rigid stainless steel or flexible molded whips
- Easy to install both inside and outside the vehicle
- Modular design for interchangeability
- Multiple cable types & connector

APPLICATIONS

- Public Safety
- PMR
- TETRA & TETRAPOL



SPECIFICATIONS

BASE		ANTENNA	
Height Above Ground	23 mm	Pattern	Omni-Directional
Installation Hole Dia	18 mm	Maximum Power	50 Watts
Operating Temperature	-40°C - 85°C	Nominal Impedance	50 Ohm
Body Material	HDPE (UV Stabilized)	Polarization	Vertical
Lock Material	Stainless Steel	VSWR	2.0:1 measured at feed point
Gasket Material	PU UV Grade	Termination	M8
Hardware Material	Stainless Steel	Ground Plane	Ground Plane Dependant
Color	Black	Color	Black
Cable Type	RG58A/U other options are available	Material	Rigid Whip: 17-7PH Stainless Steel Flexible Whip: Polyurethane Injection Molded
Connector	Interchangeable		



Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.(0).1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

BASE SPECIFICATIONS

PART NUMBER	CABLE TYPE	CABLE LENGTH	CONNECTOR
MTEN350NA-001	ATX195 (low loss RG58)	3.5m (11.48ft)	No Connector (multiple connectors available)
MTEN500NA-001	ATX195 (low loss RG58)	5m (16.40ft)	
MTEF350NA-001	RG58A/U	3.5m (11.48ft)	
MTEF500NA-001	RG58A/U	5m (16.40ft)	
MTEG350NA-001	RG58U	3.5m (11.48ft)	
MTEG500NA-001	RG58U	5m (16.40ft)	

ANTENNA SPECIFICATIONS

MODEL	FREQUENCY RANGE (MHZ)	PEAK GAIN	OVERALL ANTENNA HEIGHT
Rigid Whip Series			
WFB300	300 MHz - 334 MHz	2 dBi	8.91 in / 22.6 cm
WFB350	350 MHz - 370 MHz	2 dBi	7.75 in / 19.7 cm
WFB380	380 MHz - 430 MHz	2 dBi	6.91 in / 17.6 cm
WFB450	450 MHz - 470 MHz	2 dBi	6.16 in / 15.7cm
WFB480	480 MHz - 520 MHz	2 dBi	5.66 in / 14.4 cm
Flexible Whip Series			
EXC3001M8-001	300 MHz - 334 MHz	2 dBi	8.25 in / 21.0 cm
EXC3501M8-001	350 MHz - 370 MHz	2 dBi	7.50 in / 19.1 cm
EXC3801M8-001	380 MHz - 430 MHz	2 dBi	6.62 in / 16.8 cm
EXC4501M8-001	450 MHz - 470 MHz	2 dBi	6.06 in / 15.4cm
EXC4801M8-001	480 MHz - 520 MHz	2 dBi	5.50 in / 14 cm

ANT-DS-TETRA-M8-Base 1013

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.