M <mark>allory</mark> Mallory	/ Sonalert Pr	oducts,Inc.	Part #: SBS	12LMMCPC
Sales Outline Drawing			Revision:	E
Specifications:			01-1-8 - CARDIAC	
Sound Level Category:	Silence	Extra Loud	Extra Loud	Extra Loud
Mode of Operation:	Silence - NO SOUND	Low Priority Alarm 2 beeps repeating @ every 21 sec	Medium Priority Alarm 3 beeps repeating @ every 9 sec	High Priority Alarm 10 beeps repeating @ every 6 sec
Loudness:		95 to 105 dB(A) Typ.	95 to 105 dB(A) Typ.	95 to 105 dB(A) Typ.
Frequency:	150 to 4000 Hz			
Connection:	Connect " + " to " + " & " - " to " - " of Power Supply	Connect "+" to "+" & "-" & L to "-" of Power Supply	Connect "+" to "+" & "-" & M to "-" of Power Supply	Connect "+" to "+" & "-" & H to "-" of Power Supply
Voltage Rating:		9 to <sup>-</sup>	12 VDC	
Average Current Draw:	<40mA Typ.	<70mA Typ.	<100mA Typ.	<200mA Typ.
Ipk Current*:	630mA			
Housing Material:	ABS 777D Plastic Resin, Black			
Storage Temperature:	-40° to +85° C			
Operating Temperature:	-30° to +65° C			
Weight Typical: Options:	1.1 oz (32g)  Please contact factory.			
				DOLLC Compliant
Dimensions: Inches [m	=	cUL Recognized		ROHS Compliant
Before Code Date: 1546	Not cUL Recognized	IT NUMBER: 7880593 After Co	ode Date: 1547	cUL Recognized
	_ Ø1.750 [Ø	44.45]	0.334 [8.48]	
	0.100 [2. 0.590 [15.00	0.200 [5.08	Ø0. 5 H	Nedical No.99] Holes Req'd P [5.82]

tolerances:

±0.005 [±0.13]

\*Ipk = Instantaneous Peak