

## **Specification Sheet**

Part Number: 181-22013



Solid Wall Wiring Duct, 2" X 2", Non-Adhesive, PVC, White, 120ft/Carton

| Article Number      | 181-22013  |
|---------------------|--|
| Туре                | SD2X2  |
| Color               | White (WH)   |
| Features & Benefits | • Solid wall construction provides excellent coverage to keep wires clean. • Durable material protects wires from damage, with long-lasting performance. • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Available standard colors complement or contrast in light and dark environments. • Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement (Covers to be purchased separately.) |
| Quantity Per        | carton   |

|                                  | protects wire. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths. |
|----------------------------------|--|
| Short Description                | Solid Wall Wiring Duct, 2" X 2", Non-Adhesive, PVC, White, 120ft/Carton  |
| Global Part Name                 | SD2X2-PVC-WH   |
| Technical Description            | Non-Adhesive   |
|                                  |  |
| Length L (Imperial)              | 6.0  |
| Length L (Metric)                | 1.83   |
| Width W (Imperial)               | 2.0  |
| Width W (Metric)                 | 50.8   |
| Height H (Imperial)              | 2.07   |
| Height H (Metric)                | 52.60  |
| Mounting Hole Centers (Imperial) | 4.0  |
|                                  |  |
| Material                         | Polyvinylchloride (PVC)  |

PVC

Self-Extinguishing

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and

**Product Description** 

**Material Shortcut** 

Flammability

| Halogen free                    | No   |
|---------------------------------|--|
| Operating Temperature (Metric)  | +122°F (+50°C)                                   |
| Reach Complaint(Article 33)     | No   |
| ROHS Complaint                  | Yes  |
| Certification/Specification WEB | EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL CSA |
| UL Recognized (US)              | Yes  |
|                                 |  |
| Package Quantity(Imperial)      | 120  |
| Package Quantity (Metric)       | 36.58  |
| Customs Number                  | 3925900000                                       |

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

<sup>© 2018</sup> HellermannTyton. All rights reserved.